



PRODUCT-DETAILS

S203C-C2

S203C-C2 Miniature circuit breaker - 3P - C - 2 A



General Information	
Extended Product Type	S203C-C2
Product ID	2CDS253280R0024
EAN	4053546045000
Catalog Description	S203C-C2 Miniature circuit breaker - 3P - C - 2 A
Long Description	The S203C series miniature circuit breaker is a 3P device in 2 modules for the protection of circuits against overload and short circuit.

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 84 %
End of Life Instructions	9AKK108468A3913

Eco Transparency

Environmental Product Declaration - EPD	9AKK108467A5789
---	-----------------

Technical

Standards	IEC/EN 60898-1
Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 415 V
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Input Voltage Type	AC
Rated Current (I _n)	2 A
Rated Short-Circuit Capacity	(230 V) 6 kA (400 V) 6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(230 V) 6 kA (400 V) 6 kA
Rated Conditional Short-Circuit Current (I _{nc})	(230 V) 6 kA (400 V) 6 kA
Rated Frequency (f)	50/60 Hz
Power Loss	3.3 W
Power Supply Connection	Arbitrary
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	3
Number of Poles	3
Overvoltage Category	III
Options Provided	G2C accessories
Accessories Available	Yes
Connecting Capacity	Flexible 1 ... 10 mm ² Rigid 1 ... 16 mm ²

Material Compliance

RoHS Information	9AKK107492A9802
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20191001
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... 55 °C
Degree of Protection	IP20

Pollution Degree	2
------------------	---

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	36 mm
Product Net Height	86 mm
Product Net Depth / Length	70 mm
Product Net Weight	0.32 kg
Built-In Depth (t ₂)	70 mm

Ordering

Package Level 1 Units	carton 6 piece
Package Level 1 Gross Weight	1.97 kg
E-Number (Finland)	3212045
E-Number (Sweden)	2100911

Certificates and Declarations

Certification Agency	EN IEC
Declaration of Conformity - CE	9AKK107492A9802

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	9AKK107492A9936
-----------------------------------	-----------------

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 20 10
UNSPSC	39121614
eClass	V11.0 : 27141901
Object Classification Code	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200931R0001	G2C-H6-L+R Signal / Auxiliary Contact	G2C-H6-L+R	1	piece
2CDS200932R0001	G2C-S/H6-L+R Signal / Auxiliary Contact	G2C-S/H6-L+R	1	piece
2CDS200932R0011	G2C-S/H6-L+R-KL Signal / Auxiliary Contact	G2C-S/H6-L+R-KL	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

