



PRODUCT-DETAILS

S20/50M
50M X S20 CONDUIT



General Information	
Extended Product Type	S20/50M
Product ID	7TCA296010R0067
EAN	5020963000065
Catalog Description	50M X S20 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 20.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Length 50 Meters, Galvanised Steel General Purpose

Additional Information	
Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963000065
UPC	786210251424

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Material	Galvanized Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.84 in 250 mm
Package Level 1 Depth / Length	16.33 in 415 mm
Package Level 1 Width	16.33 in 415 mm

Certificates and Declarations	
Data Sheet, Technical Information	S20/50M
Instructions and Manuals	S20/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

