



PRODUCT-DETAILS

S25/10M
GALV.STEEL S SUPERFLEX NC25 10MT



General Information	
Extended Product Type	S25/10M
Product ID	7TCA296010R0086
EAN	5020963001468
Catalog Description	GALV.STEEL S SUPERFLEX NC25 10MT
Long Description	Inherent Low Fire Hazard Steel Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 10 Meters, Galvanised Steel General Purpose

Additional Information	
Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963001468
UPC	786210251462

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Material	Galvanized Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	5 in 127 mm
Package Level 1 Depth / Length	13 in 330 mm
Package Level 1 Width	13 in 330 mm

Certificates and Declarations	
Data Sheet, Technical Information	S25/10M
Instructions and Manuals	S25/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

