S2C-A1U 1/3



PRODUCT-DETAILS

S2C-A1U S2C-A1U Shunt Trip



General Information	
Extended Product Type	S2C-A1U
Product ID	2CDS200908R0001
EAN	4016779644723
Catalog Description	S2C-A1U Shunt Trip
Long Description	Remote opening of the device when a voltage is applied. Shunt trip only for range S 200 U and S 200 UP acc. UL 489 and CSA 22.2 No. 5.

Technical	
Standards	CSA 22.2 No. 5 UL 489
Function	Shunt Trip
Suitable For	\$200U \$200UP
Suitable for Product Class	Miniature Circuit Breaker
Power Loss	0 W

S2C-A1U 2/3

Material Compliance	
RoHS Information	2CDK400627D270
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
REACH Declaration	9AKK108468A964
REACH Information	False - does not contains substances > 0.1 mass percentag
Conflict Minerals Reporting Template (CMRT)	9AKK108468A336
SCIP	4906475e-2b37-45cb-918c-db295dd155a2 Germany (DE
Product Net Width	17.5 mr
Product Net Height	111 mr
Product Net Depth / Length	69 mr
Product Net Weight	0.133 kg
Ordering	
Package Level 1 Units	carton 1 piec
Package Level 1 Gross Weight	0.138 k
Declaration of Conformity - CE Declaration of Conformity - UKCA	2CDK400627D270 9AKK108467A548
 Installation	
Instructions and Manuals	GHS2007010P000
Popular Downloads	
Data Sheet, Technical Information	2CSC000001D020
Classifications	
ETIM 8	EC001286 - Auxiliary device for distribution board device
ETIM 9	EC001286 - Auxiliary device for distribution board device
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
WEEE B2C / B2B	Business To Busines
CN8	8536 50 8
UNSPSC	3912160
eClass	V11.0 : 2714350
IDEA Granular Category	4879 >> Shunt release (for power circuit breake
Code (IGCC)	

Code (IGCC)

S2C-A1U 3/3

Object Classification Q
Code

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Miniature\ Circuit\ Breakers\ MCBs\ \rightarrow\ Miniature\ Circuit\ Breakers\ MCBs\ \rightarrow\ Miniature\ Circuit\ Breakers\ MCBs\ Accessories\ \rightarrow\ Shunt\ Trips$









360