



PRODUCT-DETAILS

S40/25M
GALV.STEEL S SUPERFLEX NC40 25MT



General Information	
Extended Product Type	S40/25M
Product ID	7TCA296010R0140
EAN	5020963003639
Catalog Description	GALV.STEEL S SUPERFLEX NC40 25MT
Long Description	Inherent Low Fire Hazard Steel Conduit, 1-1/4 Inch, Nominal Conduit Size 40mm, Outside Diameter 42.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 25 Meters, Galvanised Steel General Purpose

Additional Information	
Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963003639
UPC	786210251561

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Galvanized Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.37 in 238 mm
Package Level 1 Depth / Length	19.25 in 489 mm
Package Level 1 Width	19.25 in 489 mm

Certificates and Declarations	
Data Sheet, Technical Information	S40/25M
Instructions and Manuals	S40/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

