



PRODUCT-DETAILS

S40/50M
GALV.STEEL S SUPERFLEX NC40 50MT



Product image
not available

General Information	
Extended Product Type	S40/50M
Product ID	7TCA296000R2525
EAN	5020963018121
Catalog Description	GALV.STEEL S SUPERFLEX NC40 50MT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 40mm, Outside Diameter 42.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 50 Meters, Galvanised Steel General Purpose

Additional Information	
Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963018121
UPC	786210293882

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Material	Galvanized Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	19.69 in 500 mm
Package Level 1 Depth / Length	29.53 in 750 mm
Package Level 1 Width	29.53 in 750 mm

Certificates and Declarations	
Data Sheet, Technical Information	S40/50M
Instructions and Manuals	S40/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available