



PRODUCT-DETAILS

S63/10M
GALV.STEEL S SUPERFLEX NC63 10MT



General Information	
Extended Product Type	S63/10M
Product ID	7TCA296010R0169
EAN	5020963005275
Catalog Description	GALV.STEEL S SUPERFLEX NC63 10MT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 63mm, Outside Diameter 62.5mm, Inside Diameter 57.5mm, Static Bend Radius 115mm, Reel Length 10 Meters, Galvanised Steel General Purpose

Additional Information	
Application	Indoors / Outdoors - Light Industrial, Buildings
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963005275
UPC	786210251639

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Material	Galvanized Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.37 in 238 mm
Package Level 1 Depth / Length	19.25 in 489 mm
Package Level 1 Width	19.25 in 489 mm

Certificates and Declarations	
Data Sheet, Technical Information	S63/10M
Instructions and Manuals	S63/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

