



PRODUCT-DETAILS

SB10/25M
STEEL BRAIDED COND NC10 25M



General Information	
Extended Product Type	SB10/25M
Product ID	7TCA296040R0014
EAN	5020963061271
Catalog Description	STEEL BRAIDED COND NC10 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 10mm, Outside Diameter 10.0mm, Inside Diameter 6.8mm, Static Bend Radius 25mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid

Additional Information	
Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963061271
UPC	786210275598

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core and Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	9 in 229 mm
Package Level 1 Width	9 in 229 mm

Certificates and Declarations	
Data Sheet, Technical Information	SB10/25M
Instructions and Manuals	SB10/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

