



PRODUCT-DETAILS

SB20/25M  
STEEL BRAIDED COND NC20 25M



| General Information   |                                                                                                                                                                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | SB20/25M                                                                                                                                                                                                                            |
| Product ID            | 7TCA296040R0040                                                                                                                                                                                                                     |
| EAN                   | 5020963001093                                                                                                                                                                                                                       |
| Catalog Description   | STEEL BRAIDED COND NC20 25M                                                                                                                                                                                                         |
| Long Description      | Low Fire Hazard, High Flexibility, Covered Steel Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid |

| Additional Information |                                                                          |
|------------------------|--------------------------------------------------------------------------|
| Application            | Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance |
| Product Type           | Low Fire Hazard Conduit                                                  |

| Ordering |               |
|----------|---------------|
| EAN      | 5020963001093 |
| UPC      | 786210244273  |

| Dimensions                 |      |
|----------------------------|------|
| Product Net Depth / Length | 25 m |

| Technical           |                                     |
|---------------------|-------------------------------------|
| Number of Batteries | 0                                   |
| Material            | Galvanized Steel Core and Overbraid |

| Environmental |                           |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |

| Container Information          |                 |
|--------------------------------|-----------------|
| Package Level 1 Units          | 1 piece         |
| Package Level 1 Height         | 7 in<br>178 mm  |
| Package Level 1 Depth / Length | 13 in<br>330 mm |
| Package Level 1 Width          | 13 in<br>330 mm |

| Certificates and Declarations     |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | SB20/25M        |
| Instructions and Manuals          | SB20/25M        |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| RoHS Information                  | 9AKK107992A8994 |
| RoHS Date                         | 9AKK107992A8994 |
| REACH Declaration                 | 9AKK107992A8994 |

| Classifications |                                     |
|-----------------|-------------------------------------|
| ETIM 8          | EC001179 - Protective metallic hose |
| UNSPSC          | 39131706                            |

---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

