



PRODUCT-DETAILS

SB50/10M
STEEL BRDD. S SUPERFLEX NC50 10MT



General Information	
Extended Product Type	SB50/10M
Product ID	7TCA296040R0080
EAN	5020963061998
Catalog Description	STEEL BRDD. S SUPERFLEX NC50 10MT
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, 1-1/2 Inch, Nominal Conduit Size 50mm, Outside Diameter 56.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel Core and Overbraid

Additional Information	
Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963061998
UPC	786210245034

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core and Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.84 in 250 mm
Package Level 1 Depth / Length	16.33 in 415 mm
Package Level 1 Width	16.33 in 415 mm

Certificates and Declarations	
Data Sheet, Technical Information	SB50/10M
Instructions and Manuals	SB50/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

