



PRODUCT-DETAILS

SN201 L-B32

SN201 L-B32 Miniature circuit breaker - 1+NP - B - 32 A



General Information	
Extended Product Type	SN201 L-B32
Product ID	2CSS245101R0325
EAN	8012542088059
Catalog Description	SN201 L-B32 Miniature circuit breaker - 1+NP - B - 32 A
Long Description	The SN201 series miniature circuit breaker is a 1P+N device in 1 module for the protection of circuits against overload and short circuit. Neutral is on the right

Technical	
Standards	IEC/EN 60898-1
Tripping Characteristic	B
Rated Voltage (U _r)	230 V AC
Rated Operational Voltage	acc. to IEC 60898-1 230 V
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Dielectric Test Voltage	2 kV
Primary Rated Impulse Withstand Voltage	4 kV

Input Voltage Type	AC
Rated Current (I _n)	32 A
Rated Short-Circuit Capacity	(230 V) 4.5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(230 V) 6 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(230 V AC) 4.5 kA
Rated Frequency (f)	50/60 Hz
Power Loss	6.7 W
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	1
Number of Poles	1+N
Number of Modular Spacings per DIN Rail	1
Overvoltage Category	III
Position of Neutral Terminals	Right
Tightening Torque	1.2 N·m
Accessory Type	Auxiliary contact Signal contact / auxiliary contact Shunt trip Undervoltage release
Actuator Type	Toggle - Insulation group IIIA, black, sealable in ON-OFF positions
Housing Type	Insulation group II, RAL 7035
Screw Terminal Type	Cage Terminal
Mounting Position	Any
Accessories Available	Yes
Connecting Capacity	Flexible 1 ... 10 mm² Rigid 1 ... 16 mm²
Wire Stripping Length	11 mm
Terminal Type	Screw Terminals

Material Compliance

RoHS Information	9AKK106713A5572
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20190722
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25 ... 55 °C
Reference Ambient Air Temperature	30 °C
Degree of Protection	IP20
Pollution Degree	2
Environmental Conditions	28 cycles ;with 55 °C / 90-96 % ;and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g or 0.35mm 5 ... 150 ... 5 Hz

Resistance to Shock acc. to IEC 60068-2-27	30g 2 shocks 13 ms
Environmental Information	refer to RoHS information

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	0.018 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.110 kg
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	box 6 piece
Package Level 1 Gross Weight	0.684 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5572
-----------------------------------	-----------------

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	2CSC400002D0209
--------------------------------------	-----------------

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85362010
eClass	V11.0 : 27141901
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

