SP16/OR/25M 1/3



PRODUCT-DETAILS

SP16/OR/25M PVC COVRD.LIQ.PROOF NC16 25MT ORN



Extended Product Type	SP16/OR/25M
Product ID	7TCA296020R0110
EAN	502096300305
Catalog Description	PVC COVRD.LIQ.PROOF NC16 25MT ORN
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, 3/8 Inch, Nominal Conduit Size 16mm, Outside Diameter 17.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 25 Meters. PVC Jacket with Galvanised Steel Core, Orange
Additional Information	
Additional Information	Indoors / Outdoors - Light Industrial General Purpose, Buildings
Additional Information Application Product Type	
Application	
Application	
Application Product Type	Indoors / Outdoors - Light Industrial, General Purpose, Buildings High Flexibility Condui

SP16/OR/25M 2/3

Dimensions	
Product Net Depth / Length	25 m
Technical	
Number of Batteries	0
Color	Orange
<u>Material</u>	Galvanized Steel Core with PVC Jacket
 Environmental	
WEEE Category	Product Not in WEEE Scope
Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	6 in 152 mm
Package Level 1 Depth /	13 in
Length	330 mm
Package Level 1 Width	13 in 330 mm
Certificates and Declarations	
Data Sheet, Technical Information	SP16/OR/25M
Instructions and Manuals	SP16/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994
Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

<u> </u>	
Cated	iories
Oaice	101163

SP16/OR/25M 3/3

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$

