



PRODUCT-DETAILS

SP20/GR/25M
25M X SP20/GREY CONDUIT



General Information	
Extended Product Type	SP20/GR/25M
Product ID	7TCA296020R0147
EAN	5020963003080
Catalog Description	25M X SP20/GREY CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Grey
Additional Information	
Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Product Type	High Flexibility Conduit
Ordering	
EAN	5020963003080
UPC	786210275567

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Gray
Material	Galvanized Steel Core with PVC Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	13 in 330 mm
Package Level 1 Width	13 in 330 mm

Certificates and Declarations	
Data Sheet, Technical Information	SP20/GR/25M
Instructions and Manuals	SP20/GR/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

