



PRODUCT-DETAILS

SP25/BL/50M
50M X SP25/BLACK CONDUIT



General Information	
Extended Product Type	SP25/BL/50M
Product ID	7TCA296020R0186
EAN	5020963000133
Catalog Description	50M X SP25/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 50 Meters, PVC Jacket with Galvanised Steel Core, Black

Additional Information	
Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Product Type	High Flexibility Conduit

Ordering	
EAN	5020963000133
UPC	786210249087

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	12 in 305 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SP25/BL/50M
Instructions and Manuals	SP25/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

