



PRODUCT-DETAILS

SP32/BL/25M
25M X SP32/BLACK CONDUIT



General Information	
Extended Product Type	SP32/BL/25M
Product ID	7TCA296020R0227
EAN	5020963000140
Catalog Description	25M X SP32/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, 1 Inch, Nominal Conduit Size 32mm, Outside Diameter 34.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Black

Additional Information	
Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Product Type	High Flexibility Conduit

Ordering	
EAN	5020963000140
UPC	786210249162

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	12 in 305 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SP32/BL/25M
Instructions and Manuals	SP32/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

