



PRODUCT-DETAILS

SPB12/25M
STEEL BRDD SP LIQ.PROOF NC12 25MT



General Information	
Extended Product Type	SPB12/25M
Product ID	7TCA296040R0102
EAN	5020963004803
Catalog Description	STEEL BRDD SP LIQ.PROOF NC12 25MT
Long Description	Highly Flexible Steel Conduit, 5/16 Inch, Nominal Conduit Size 12mm, Outer Diameter 14.0mm, Inner Diameter 10.3mm, Maximum Bend Radius 30mm, Reel Length 25 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

Additional Information	
Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Product Type	High Flexibility Conduit

Ordering	
EAN	5020963004803
UPC	786210258911

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core and Overbraid with PVC Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	5 in 127 mm
Package Level 1 Depth / Length	13 in 330 mm
Package Level 1 Width	13 in 330 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPB12/25M
Instructions and Manuals	SPB12/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

