



PRODUCT-DETAILS

SPB32/10M
STEEL BRDD SP LIQ.PROOF NC32 10MT



General Information	
Extended Product Type	SPB32/10M
Product ID	7TCA296040R0146
EAN	5020963005213
Catalog Description	STEEL BRDD SP LIQ.PROOF NC32 10MT
Long Description	Highly Flexible Steel Conduit, 1 Inch, Nominal Conduit Size 32mm, Outer Diameter 34.0mm, Inner Diameter 28.1mm, Maximum Bend Radius 60mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

Additional Information	
Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Product Type	High Flexibility Conduit

Ordering	
EAN	5020963005213
UPC	786210245317

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core and Overbraid with PVC Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	6 in 152 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPB32/10M
Instructions and Manuals	SPB32/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

