



PRODUCT-DETAILS

SPB40/10M
STEEL BRDD SP LIQ.PROOF NC40 10MT



General Information	
Extended Product Type	SPB40/10M
Product ID	7TCA296040R0156
EAN	5020963008221
Catalog Description	STEEL BRDD SP LIQ.PROOF NC40 10MT
Long Description	Highly Flexible Steel Conduit, 1-1/4 Inch, Nominal Conduit Size 40mm, Outer Diameter 43.6mm, Inner Diameter 37.7mm, Maximum Bend Radius 80mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

Additional Information	
Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Product Type	High Flexibility Conduit

Ordering	
EAN	5020963008221
UPC	786210245348

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core and Overbraid with PVC Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.37 in 238 mm
Package Level 1 Depth / Length	19.25 in 489 mm
Package Level 1 Width	19.25 in 489 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPB40/10M
Instructions and Manuals	SPB40/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

