



PRODUCT-DETAILS

SPL-EF12/10M
ENHAN.FIRE LIQ.TIGHT NC12 10MT BLK



Product image
not available

General Information	
Extended Product Type	SPL-EF12/10M
Product ID	7TCA296030R0467
EAN	5020963802775
Catalog Description	ENHAN.FIRE LIQ.TIGHT NC12 10MT BLK
Long Description	Liquidtight, High Flexibility Conduit, 5/16 Inch, Nominal Conduit Size 12mm, Outside Diameter 14.2mm, Inside Diameter 12.0mm, Static Bend Radius 45mm, Enhanced Fire Performance, Galvanised Steel Core, Reel Length 10 Meters, Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Highly Flexible Conduit

Ordering	
EAN	5020963802775
UPC	786210314501

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL-EF12/10M
Instructions and Manuals	SPL-EF12/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available