



PRODUCT-DETAILS

SPL-EF32/10M
ENHAN.FIRE LIQ.TIGHT NC32 10MT BLK



Product image
not available

General Information	
Extended Product Type	SPL-EF32/10M
Product ID	7TCA296030R0481
EAN	5020963802881
Catalog Description	ENHAN.FIRE LIQ.TIGHT NC32 10MT BLK
Long Description	Liquidtight, High Flexibility Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Enhanced Fire Performance, Galvanised Steel Core, Reel Length 10 Meters, Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Highly Flexible Conduit

Ordering	
EAN	5020963802881
UPC	786210315362

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.37 in 238 mm
Package Level 1 Depth / Length	19.25 in 489 mm
Package Level 1 Width	19.25 in 489 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL-EF32/10M
Instructions and Manuals	SPL-EF32/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available