



PRODUCT-DETAILS

SPL-EF32/50M
ENHAN.FIRE LIQ.TIGHT NC32 50MT BLK



General Information	
Extended Product Type	SPL-EF32/50M
Product ID	7TCA296030R0479
EAN	5020963802904
Catalog Description	ENHAN.FIRE LIQ.TIGHT NC32 50MT BLK
Long Description	Liquidtight, High Flexibility Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Enhanced Fire Performance, Galvanised Steel Core, Reel Length 50 Meters, Black
Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Highly Flexible Conduit
Ordering	
EAN	5020963802904
UPC	786210314600

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	32.28 in 820 mm
Package Level 1 Width	32.28 in 820 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL-EF32/50M
Instructions and Manuals	SPL-EF32/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available