



PRODUCT-DETAILS

SPL-EF40/10M
ENHAN.FIRE LIQ.TIGHT NC40 10MT BLK



General Information	
Extended Product Type	SPL-EF40/10M
Product ID	7TCA296030R0482
EAN	5020963802911
Catalog Description	ENHAN.FIRE LIQ.TIGHT NC40 10MT BLK
Long Description	Liquidtight, High Flexibility Conduit, 1-1/4 Inch, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Enhanced Fire Performance, Galvanised Steel Core, Reel Length 10 Meters, Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Highly Flexible Conduit

Ordering	
EAN	5020963802911
UPC	786210314242

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	26.77 in 680 mm
Package Level 1 Width	26.77 in 680 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL-EF40/10M
Instructions and Manuals	SPL-EF40/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

