SPL10/50M 1/3



PRODUCT-DETAILS

SPL10/50M

OIL RES UR LIQ.TIGHT NC10 50MT BLK



General Information	
Extended Product Type	SPL10/50M
Product ID	7TCA296030R0042
EAN	5020963001246
Catalog Description	OIL RES UR LIQ.TIGHT NC10 50MT BLK
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, 1/4 Inch, Nominal Conduit Size 10mm, Outside Diameter 11.8mm, Inside Diameter 7.0mm, Static Bend Radius 40mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit
Ordering	
EAN	5020963001246
UPC	786210274867

SPL10/50M 2/3

Dı	m	е	n	SI	0	ns

Product Net Depth / 50 m Length

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Covering

Environmental

WEEE Category Product Not in WEEE Scope

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	6 in
	152 mm
Package Level 1 Depth /	16 in
Length	406 mm
Package Level 1 Width	16 in
	406 mm

Certificates and Declarations

Data Sheet, Technical Information	SPL10/50M
Instructions and Manuals	SPL10/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

SPL10/50M 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$

