



PRODUCT-DETAILS

SPL12/10M
OIL RES UR LIQ.TIGHT NC12 10MT BLK



General Information	
Extended Product Type	SPL12/10M
Product ID	7TCA296030R0054
EAN	5020963007286
Catalog Description	OIL RES UR LIQ.TIGHT NC12 10MT BLK
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.2mm, Inside Diameter 10.0mm, Static Bend Radius 45mm, Reel Length 10 Meters, PVC Covering with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering	
EAN	5020963007286
UPC	786210245829

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL12/10M
Instructions and Manuals	SPL12/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

