




---

 PRODUCT-DETAILS

# SPL12/25M

## OIL RES UR LIQ.TIGHT NC12 25MT BLK




---

**General Information**

Extended Product Type	SPL12/25M
Product ID	7TCD012980R0287
EAN	5415022064643
Catalog Description	OIL RES UR LIQ.TIGHT NC12 25MT BLK
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, 5/16 Inch, Nominal Conduit Size 12mm, Outside Diameter 14.2mm, Inside Diameter 10.0mm, Static Bend Radius 45mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

---

**Additional Information**

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

---

**Ordering**

EAN	5415022064643
UPC	786209985156

---

## Dimensions

Product Net Depth / Length	25 m
----------------------------	------

---



---

## Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Covering

---



---

## Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

---



---

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

---



---

## Certificates and Declarations

Data Sheet, Technical Information	SPL12/25M
Instructions and Manuals	SPL12/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

---



---

## Classifications

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

---

---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

