



PRODUCT-DETAILS

SPL16/50M
OIL RES UR LIQ.TIGHT NC16 50MT BLK



General Information	
Extended Product Type	SPL16/50M
Product ID	7TCA296030R0080
EAN	5020963000782
Catalog Description	OIL RES UR LIQ.TIGHT NC16 50MT BLK
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, 3/8 Inch, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering	
EAN	5020963000782
UPC	786210246765

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10 in 254 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL16/50M
Instructions and Manuals	SPL16/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

