



PRODUCT-DETAILS

SPL16/GR/25M
OIL RES UR LIQ.TIGHT NC16 25MT GRY



General Information	
Extended Product Type	SPL16/GR/25M
Product ID	7TCA296030R0085
EAN	5020963007279
Catalog Description	OIL RES UR LIQ.TIGHT NC16 25MT GRY
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 25 Meters. PVC Covering with Galvanised Steel Core, Grey

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering	
EAN	5020963007279
UPC	786210258997

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Gray
Material	Galvanized Steel Core with PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	6 in 152 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL16/GR/25M
Instructions and Manuals	SPL16/GR/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

