



PRODUCT-DETAILS

SPL20/GR/25M
OIL RES UR LIQ.TIGHT NC20 25MT GRY



General Information	
Extended Product Type	SPL20/GR/25M
Product ID	7TCA296030R0151
EAN	5020963006524
Catalog Description	OIL RES UR LIQ.TIGHT NC20 25MT GRY
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters. PVC Covering with Galvanised Steel Core. Grey

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering	
EAN	5020963006524
UPC	786210239408

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Gray
Material	Galvanized Steel Core with PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	8 in 203 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL20/GR/25M
Instructions and Manuals	SPL20/GR/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

