



PRODUCT-DETAILS

SPL25/50M
50M X SPL25/BLACK CONDUIT



General Information	
Extended Product Type	SPL25/50M
Product ID	7TCA296030R0195
EAN	5020963000324
Catalog Description	50M X SPL25/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering	
EAN	5020963000324
UPC	786210247069

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.37 in 238 mm
Package Level 1 Depth / Length	19.25 in 489 mm
Package Level 1 Width	19.25 in 489 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL25/50M
Instructions and Manuals	SPL25/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

