



PRODUCT-DETAILS

SPL40/GR/25M

OIL RES UR LIQ.TIGHT NC40 25MT GRY



General Information	
Extended Product Type	SPL40/GR/25M
Product ID	7TCA296030R0278
EAN	5020963798924
Catalog Description	OIL RES UR LIQ.TIGHT NC40 25MT GRY
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, 1-1/4 Inch, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 10 Meters. PVC Covering with Galvanised Steel Core. Grey
Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit
Ordering	
EAN	5020963798924
UPC	786210293646

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Gray
Material	Galvanized Steel Core with PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	32.28 in 820 mm
Package Level 1 Width	32.28 in 820 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL40/GR/25M
Instructions and Manuals	SPL40/GR/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available