



PRODUCT-DETAILS

SPL50/10M
OIL RES UR LIQ.TIGHT NC50 10MT BLK



General Information	
Extended Product Type	SPL50/10M
Product ID	7TCA296030R0289
EAN	5020963002885
Catalog Description	OIL RES UR LIQ.TIGHT NC50 10MT BLK
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, 1-1/2 Inch, Nominal Conduit Size 50mm, Outside Diameter 47.5mm, Inside Diameter 40.4mm, Static Bend Radius 240mm, Reel Length 10 Meters. PVC Covering with Galvanised Steel Core. Black

Additional Information	
Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering	
EAN	5020963002885
UPC	786210247267

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	26.77 in 680 mm
Package Level 1 Width	26.77 in 680 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPL50/10M
Instructions and Manuals	SPL50/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

