



PRODUCT-DETAILS

SPLHC12/70M
XTR.TEMP UR LIQ.TIGHT NC12 70MT BLK



General Information	
Extended Product Type	SPLHC12/70M
Product ID	7TCA296030R0388
EAN	5020963799983
Catalog Description	XTR.TEMP UR LIQ.TIGHT NC12 70MT BLK
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 12mm, 5/16 Inch US Conduit Size, Outside Diameter 14.2mm, Inside Diameter 12.0mm, Static Bend Radius 45mm, Reel Length 70 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering	
EAN	5020963799983
UPC	786210313979

Dimensions	
Product Net Depth / Length	70 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Thermoplastic Rubber Cover

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPLHC12/70M
Instructions and Manuals	SPLHC12/70M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

