



PRODUCT-DETAILS

SPLHC63/25M
XTR.TEMP UR LIQ.TIGHT NC63 25MT BLK



General Information	
Extended Product Type	SPLHC63/25M
Product ID	7TCA296030R0360
EAN	5020963028267
Catalog Description	XTR.TEMP UR LIQ.TIGHT NC63 25MT BLK
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 63mm, Outside Diameter 59.7mm, Inside Diameter 51.6mm, Static Bend Radius 345mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering	
EAN	5020963028267
UPC	786210245737

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Thermoplastic Rubber Cover

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	32.28 in 820 mm
Package Level 1 Width	32.28 in 820 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPLHC63/25M
Instructions and Manuals	SPLHC63/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

