



PRODUCT-DETAILS

SPLHCB25/25M

STL BRAIDED SPLHC25 FLEX 25M



General Information	
Extended Product Type	SPLHCB25/25M
Product ID	7TCA296100R0171
EAN	5020963011023
Catalog Description	STL BRAIDED SPLHC25 FLEX 25M
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit with Stainless Steel Overbraid, Medium Flexibility, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering	
EAN	5020963011023
UPC	786210245515

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Thermoplastic Rubber Cover

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10 in 254 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPLHCB25/25M
Instructions and Manuals	SPLHCB25/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

