



PRODUCT-DETAILS

SPLHCB40/10M
BRDD.XTR.TEMP LQ.TIGH NC40 10MT BLK



General Information	
Extended Product Type	SPLHCB40/10M
Product ID	7TCA296100R0174
EAN	5020963050275
Catalog Description	BRDD.XTR.TEMP LQ.TIGH NC40 10MT BLK
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit with Stainless Steel Braid, Medium Flexibility, Nominal Conduit Size 40mm, 1-1/4 Inch US Conduit Size, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 10 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Additional Information	
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering	
EAN	5020963050275
UPC	786210245553

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Thermoplastic Rubber Cover

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	26.77 in 680 mm
Package Level 1 Width	26.77 in 680 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPLHCB40/10M
Instructions and Manuals	SPLHCB40/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

