



PRODUCT-DETAILS

SPTC20/25M
TIN COP.BRDD LQ.PROOF NC20 25MT BLK



General Information	
Extended Product Type	SPTC20/25M
Product ID	7TCA296100R0184
EAN	5020963010859
Catalog Description	TIN COP.BRDD LQ.PROOF NC20 25MT BLK
Long Description	Highly Flexible Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, Galvanised Steel Core with PVC Jacket and Tinned Copper Overbraid, Black

Additional Information	
Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Product Type	High Flexibility Conduit

Ordering	
EAN	5020963010859
UPC	786210247434

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core, Tinned Copper Overbraid with PVC Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPTC20/25M
Instructions and Manuals	SPTC20/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

