



PRODUCT-DETAILS

SPUL20/50M
50M X SPUL20/GREY CONDUIT



General Information	
Extended Product Type	SPUL20/50M
Product ID	7TCA296030R0367
EAN	5020963003851
Catalog Description	50M X SPUL20/GREY CONDUIT
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 50 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey

Additional Information	
Application	Flexible Protection Systems
Product Type	Liquid Tight, Medium Flexibility Conduit

Ordering	
EAN	5020963003851
UPC	786210247564

Dimensions	
Product Net Depth / Length	50 m

Technical	
Number of Batteries	0
Color	Gray
Material	Galvanized Steel Core with PVC Cover and Copper Packing

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations	
Data Sheet, Technical Information	SPUL20/50M
Instructions and Manuals	SPUL20/50M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

