



PRODUCT-DETAILS

SPUL25/BL/25M  
UL-CSA LIST LIQ.TIGHT NC25 25MT BLK



| General Information   |                                                                                                                                                                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | SPUL25/BL/25M                                                                                                                                                                                                                                                                            |
| Product ID            | 7TCA296030R0427                                                                                                                                                                                                                                                                          |
| EAN                   | 5020963801181                                                                                                                                                                                                                                                                            |
| Catalog Description   | UL-CSA LIST LIQ.TIGHT NC25 25MT BLK                                                                                                                                                                                                                                                      |
| Long Description      | Liquid Tight, Medium Flexibility, Covered Steel Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 105mm, Reel Length 25 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Black |

| Additional Information |                                          |
|------------------------|------------------------------------------|
| Application            | Flexible Protection Systems              |
| Product Type           | Liquid Tight, Medium Flexibility Conduit |

| Ordering |               |
|----------|---------------|
| EAN      | 5020963801181 |
| UPC      | 786210289977  |

|                            |      |
|----------------------------|------|
| Dimensions                 |      |
| Product Net Depth / Length | 25 m |

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| Technical           |                                                         |
| Number of Batteries | 0                                                       |
| Color               | Black                                                   |
| Material            | Galvanized Steel Core with PVC Cover and Copper Packing |

|               |                           |
|---------------|---------------------------|
| Environmental |                           |
| WEEE Category | Product Not in WEEE Scope |

|                                |                    |
|--------------------------------|--------------------|
| Container Information          |                    |
| Package Level 1 Units          | 1 piece            |
| Package Level 1 Height         | 9.37 in<br>238 mm  |
| Package Level 1 Depth / Length | 19.25 in<br>489 mm |
| Package Level 1 Width          | 19.25 in<br>489 mm |

|                                   |                 |
|-----------------------------------|-----------------|
| Certificates and Declarations     |                 |
| Data Sheet, Technical Information | SPUL25/BL/25M   |
| Instructions and Manuals          | SPUL25/BL/25M   |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| RoHS Information                  | 9AKK107992A8994 |
| RoHS Date                         | 9AKK107992A8994 |
| REACH Declaration                 | 9AKK107992A8994 |

|                 |                                     |
|-----------------|-------------------------------------|
| Classifications |                                     |
| ETIM 8          | EC001179 - Protective metallic hose |
| UNSPSC          | 39131706                            |

|            |  |
|------------|--|
| Categories |  |
|------------|--|

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

