



PRODUCT-DETAILS

SPUL32/25M

FLEX COND TO UL SPEC NC32 25M



General Information	
Extended Product Type	SPUL32/25M
Product ID	7TCA296030R0370
EAN	5020963009037
Catalog Description	FLEX COND TO UL SPEC NC32 25M
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 165mm, Reel Length 25 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey

Additional Information	
Application	Flexible Protection Systems
Product Type	Liquid Tight, Medium Flexibility Conduit

Ordering	
EAN	5020963009037
UPC	786210275321

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Gray
Material	Galvanized Steel Core with PVC Cover and Copper Packing

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece

Certificates and Declarations	
Data Sheet, Technical Information	SPUL32/25M
Instructions and Manuals	SPUL32/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
-------------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

