



PRODUCT-DETAILS

SS10/25M
25M X SS10 CONDUIT



General Information	
Extended Product Type	SS10/25M
Product ID	7TCA296120R0005
EAN	5020963026027
Catalog Description	25M X SS10 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, 1/4 Inch, Nominal Conduit Size 10mm, Outside Diameter 9.0mm, Inside Diameter 6.8mm, Static Bend Radius 25mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant

Additional Information	
Application	Indoors / Outdoors - Corrosive Environments
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963026027
UPC	786210249520

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Stainless Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	9 in 229 mm
Package Level 1 Width	9 in 229 mm

Certificates and Declarations	
Data Sheet, Technical Information	SS10/25M
Instructions and Manuals	SS10/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

