



PRODUCT-DETAILS

SS12/25M  
STAIN.STEEL SS SUPERFLEX NC12 25MT



| General Information   |                                                                                                                                                                                                                   |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | SS12/25M                                                                                                                                                                                                          |
| Product ID            | 7TCA296120R0008                                                                                                                                                                                                   |
| EAN                   | 5020963005855                                                                                                                                                                                                     |
| Catalog Description   | STAIN.STEEL SS SUPERFLEX NC12 25MT                                                                                                                                                                                |
| Long Description      | Inherent Low Fire Hazard Conduit, 5/16 Inch, Nominal Conduit Size 12mm, Outside Diameter 13.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant |

| Additional Information |                                             |
|------------------------|---------------------------------------------|
| Application            | Indoors / Outdoors - Corrosive Environments |
| Product Type           | Low Fire Hazard Conduit                     |

| Ordering |               |
|----------|---------------|
| EAN      | 5020963005855 |
| UPC      | 786210249537  |

| Dimensions                 |      |
|----------------------------|------|
| Product Net Depth / Length | 25 m |

| Technical           |                 |
|---------------------|-----------------|
| Number of Batteries | 0               |
| Material            | Stainless Steel |

| Environmental |                           |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |

| Container Information          |                |
|--------------------------------|----------------|
| Package Level 1 Units          | 1 piece        |
| Package Level 1 Height         | 6 in<br>152 mm |
| Package Level 1 Depth / Length | 9 in<br>229 mm |
| Package Level 1 Width          | 9 in<br>229 mm |

| Certificates and Declarations     |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | SS12/25M        |
| Instructions and Manuals          | SS12/25M        |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| RoHS Information                  | 9AKK107992A8994 |
| RoHS Date                         | 9AKK107992A8994 |
| REACH Declaration                 | 9AKK107992A8994 |

| Classifications |                                     |
|-----------------|-------------------------------------|
| ETIM 8          | EC001179 - Protective metallic hose |
| UNSPSC          | 39131706                            |

---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

