



PRODUCT-DETAILS

SS16/25M

NC16 SS CONDUIT NW-16 LEN 25 METER



General Information	
Extended Product Type	SS16/25M
Product ID	7TCA296120R0014
EAN	5020963007224
Catalog Description	NC16 SS CONDUIT NW-16 LEN 25 METER
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 16mm, Outside Diameter 16.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant

Additional Information	
Application	Indoors / Outdoors - Corrosive Environments
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963007224
UPC	786210249544

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Stainless Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	6 in 152 mm
Package Level 1 Depth / Length	13 in 330 mm
Package Level 1 Width	13 in 330 mm

Certificates and Declarations	
Data Sheet, Technical Information	SS16/25M
Instructions and Manuals	SS16/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

