



PRODUCT-DETAILS

SS20/10M
10M X SS20 CONDUIT



General Information	
Extended Product Type	SS20/10M
Product ID	7TCA296120R0018
EAN	5020963027284
Catalog Description	10M X SS20 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 20.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 10 Meters, 316 Stainless Steel, Corrosion Resistant

Additional Information	
Application	Indoors / Outdoors - Corrosive Environments
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963027284
UPC	786210260785

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Material	Stainless Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	6 in 152 mm
Package Level 1 Depth / Length	9 in 229 mm
Package Level 1 Width	9 in 229 mm

Certificates and Declarations	
Data Sheet, Technical Information	SS20/10M
Instructions and Manuals	SS20/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

