



PRODUCT-DETAILS

SS25/25M
STAIN.STEEL SS SUPERFLEX NC25 25MT



General Information	
Extended Product Type	SS25/25M
Product ID	7TCA296120R0026
EAN	5020963008900
Catalog Description	STAIN.STEEL SS SUPERFLEX NC25 25MT
Long Description	Inherent Low Fire Hazard Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant

Additional Information	
Application	Indoors / Outdoors - Corrosive Environments
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963008900
UPC	786210249568

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Stainless Steel

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	SS25/25M
Instructions and Manuals	SS25/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
-------------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

