



PRODUCT-DETAILS

SSB12/25M
S.STL BRD S.STL COND 25M REELS



General Information	
Extended Product Type	SSB12/25M
Product ID	7TCA296100R0190
EAN	5020963052668
Catalog Description	S.STL BRD S.STL COND 25M REELS
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 25 Meters, 316 Stainless Steel Core and Overbraid

Additional Information	
Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963052668
UPC	786210260693

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Stainless Steel Core and Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	13 in 330 mm
Package Level 1 Width	13 in 330 mm

Certificates and Declarations	
Data Sheet, Technical Information	SSB12/25M
Instructions and Manuals	SSB12/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

