



PRODUCT-DETAILS

SSB20/25M

STEEL BRDD S SUPERFLEX NC20 25MT



General Information	
Extended Product Type	SSB20/25M
Product ID	7TCA296100R0192
EAN	5020963012013
Catalog Description	STEEL BRDD S SUPERFLEX NC20 25MT
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, 316 Stainless Steel Core and Overbraid
Additional Information	
Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Product Type	Low Fire Hazard Conduit
Ordering	
EAN	5020963012013
UPC	786210260716

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Stainless Steel Core and Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	13 in 330 mm
Package Level 1 Width	13 in 330 mm

Certificates and Declarations	
Data Sheet, Technical Information	SSB20/25M
Instructions and Manuals	SSB20/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
-------------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

