



PRODUCT-DETAILS

SSPLHC32/25M
XTR.TEMP 316SS LQTIGH NC32 25MT BLK



General Information	
Extended Product Type	SSPLHC32/25M
Product ID	7TCA296030R0418
EAN	5020963800931
Catalog Description	XTR.TEMP 316SS LQTIGH NC32 25MT BLK
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 32mm, 1 Inch US Conduit Size, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Stainless Steel Core, Black

Additional Information	
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering	
EAN	5020963800931
UPC	786210289816

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Stainless Steel Core with Thermoplastic Rubber Cover

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	26.77 in 680 mm
Package Level 1 Width	26.77 in 680 mm

Certificates and Declarations	
Data Sheet, Technical Information	7TKK001231
Instructions and Manuals	SSPLHC32/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available