



PRODUCT-DETAILS

SSPLHC50/10M

XTR.TEMP 316SS LQTIGH NC50 10MT BLK



General Information	
Extended Product Type	SSPLHC50/10M
Product ID	7TCA296030R0420
EAN	5020963800955
Catalog Description	XTR.TEMP 316SS LQTIGH NC50 10MT BLK
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 50mm, Outside Diameter 47.9mm, Inside Diameter 40.4mm, Static Bend Radius 240mm, Reel Length 10 Meters, Thermoplastic Rubber Cover with Stainless Steel Core, Black

Additional Information	
Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering	
EAN	5020963800955
UPC	786210289830

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Stainless Steel Core with Thermoplastic Rubber Cover

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	32.28 in 820 mm
Package Level 1 Width	32.28 in 820 mm

Certificates and Declarations	
Data Sheet, Technical Information	7TKK001231
Instructions and Manuals	SSPLHC50/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available