



PRODUCT-DETAILS

STC12/25M
STEEL T/COPPER BRD FLEX NC12 25M



General Information	
Extended Product Type	STC12/25M
Product ID	7TCA296100R0202
EAN	5020963040153
Catalog Description	STEEL T/COPPER BRD FLEX NC12 25M
Long Description	Low Fire Hazard, High Flexibility Conduit, 5/16 Inch, Nominal Conduit Size 12mm, Outside Diameter 14.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 25 Meters. Galvanised Steel Core with Tinned Copper Overbraid
Additional Information	
Application	Galvanised Steel Core with Tinned Copper Overbraid
Product Type	Low Fire Hazard Conduit
Ordering	
EAN	5020963040153
UPC	786210260822

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core with Tinned Copper Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	0.01 in 0.25 mm
Package Level 1 Depth / Length	0.01 in 0.25 mm
Package Level 1 Width	0.01 in 0.25 mm

Certificates and Declarations	
Data Sheet, Technical Information	STC12/25M
Instructions and Manuals	STC12/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories	
------------	--

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

