



PRODUCT-DETAILS

STC25/25M
TIN COP.BRDD S SUPERFLEX NC25 25MT



General Information	
Extended Product Type	STC25/25M
Product ID	7TCA296100R0206
EAN	5020963013959
Catalog Description	TIN COP.BRDD S SUPERFLEX NC25 25MT
Long Description	Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, Galvanised Steel Core with Tinned Copper Overbraid

Additional Information	
Application	Galvanised Steel Core with Tinned Copper Overbraid
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963013959
UPC	786210260853

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Material	Galvanized Steel Core with Tinned Copper Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	STC25/25M
Instructions and Manuals	STC25/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

